

MICHAUD CHAILLYELEMENTS
DE TRANSMISSIONmodèle **A9-H100**

Poulie dentée monobloc

Pas 12,7 mm (1/2") pour courroie largeur 25,4 mm

Illustration technique et photo, voir page 264.

MATIÈRE

- Acier.
- Fonte.

	● Délai maîtrisé	○ Contactez-nous											Référence
			Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	Exemple de commande A9-14H100F
Acier													
A9-14H100F	●		6F	14	12	63	56,59	55,22	40	45	31,8	0,65	
A9-15H100F	●		6F	15	12	66	60,64	59,27	45	45	31,8	0,77	
A9-16H100F	●		6F	16	12	71	64,68	63,31	45	45	31,8	0,87	
A9-17H100F	●		6F	17	12	75	68,72	67,35	45	45	31,8	0,97	
A9-18H100F	●		6F	18	12	79	72,77	71,39	55	45	31,8	1,16	
A9-19H100F	●		6F	19	14	83	76,81	75,44	60	45	31,8	1,3	
A9-20H100F	●		6F	20	14	87	80,85	79,48	62	45	31,8	1,44	
A9-21H100F	●		6F	21	14	91	84,89	83,52	65	45	31,8	1,6	
A9-22H100F	●		6F	22	14	93	88,94	87,56	68	45	31,8	1,76	
A9-23H100F	●		6F	23	14	97	92,98	91,61	72	45	31,8	1,94	
A9-24H100F	●		6F	24	14	103	97,03	95,65	72	45	31,8	2,09	
A9-25H100F	●		6F	25	14	106	101,06	99,69	72	45	31,8	2,24	
A9-26H100F	●		6F	26	14	111	105,11	103,73	80	45	31,8	2,49	
A9-27H100F	●		6F	27	14	115	109,15	107,78	80	45	31,8	2,66	
A9-28H100F	●		6F	28	14	119	113,19	111,82	80	45	31,8	2,83	
A9-29H100F	●		6F	29	14	123	117,23	115,86	80	45	31,8	3,01	
A9-30H100F	●		6F	30	14	127	121,29	119,9	80	45	31,8	3,19	
A9-32H100F	●		6F	32	14	135	129,36	127,99	80	45	31,8	3,57	

Produits associés**A8-H100** Page 228**A8-H100-CH**
Page 255**MA A9-H100**
Page 287


Poulie dentée monobloc

Pas 12,7 mm (1/2") pour courroie largeur 25,4 mm

Illustration technique et photo, voir page 264.

● Délai maîtrisé ○ Contactez-nous

■ Exemple de commande **A9-14H100F** Référence

		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg
A9-33H100F	●	6F	33	14	140	133,4	132,03	80	45	31,8	3,79
A9-34H100F	●	6F	34	14	143	137,45	136,07	80	45	31,8	3,99
A9-35H100F	●	6F	35	14	148	141,49	140,12	80	45	31,8	4,2
A9-36H100F	●	6F	36	14	152	145,53	144,16	80	45	31,8	4,44
A9-38H100F	●	6F	38	14	158	153,62	152,24	80	45	31,8	4,9
A9-40H100F	●	6F	40	14	168	161,7	160,33	80	45	31,8	5,39
Fonte											
A9-44H100F	●	6VF	44	18	184	177,87	176,5	80	50	31,8	3,37
A9-45H100F	●	6VF	45	18	192	181,91	180,54	80	50	31,8	3,57
A9-48H100F	●	6VF	48	18	200	194,04	192,67	90	50	31,8	4,1
A9-50H100	●	6A	50	18	-	202,13	200,75	90	50	31,8	4,24
A9-52H100	●	6A	52	18	-	210,21	208,84	90	50	31,8	4,32
A9-58H100	●	6A	58	18	-	234,47	233,09	90	50	31,8	4,61
A9-60H100	●	6A	60	18	-	242,55	241,18	100	50	31,8	5,3
A9-70H100	●	6A	70	18	-	282,98	281,61	100	55	31,8	6,13
A9-72H100	●	6A	72	18	-	291,06	289,69	120	55	31,8	7,47
A9-84H100	●	6A	84	18	-	339,57	338,2	120	55	31,8	8,52
A9-96H100	●	6A	96	18	-	388,08	386,71	120	60	31,8	10,25
A9-120H100	●	6A	120	18	-	485,1	483,73	120	60	31,8	13,09