

MICHAUD CHAILLYELEMENTS
DE TRANSMISSIONmodèle **A9-H200**

Poulie dentée monobloc

Pas 12,7 mm (1/2") pour courroie largeur 50,8 mm

Illustration technique et photo, voir page 264.

MATIÈRE

- Acier.
- Fonte.

	● Délai maîtrisé	○ Contactez-nous											Référence
			Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	Exemple de commande A9-14H200F
Acier													
A9-14H200F	●		6F	14	18	63	56,59	55,22	40	70	58,7	1,1	
A9-15H200F	●		6F	15	18	66	60,64	59,27	45	70	58,7	1,33	
A9-16H200F	●		6F	16	18	71	64,68	63,31	45	70	58,7	1,54	
A9-17H200F	●		6F	17	18	75	68,72	67,35	45	70	58,7	1,69	
A9-18H200F	●		6F	18	18	79	72,77	71,39	55	70	58,7	1,95	
A9-19H200F	●		6F	19	18	83	76,81	75,44	60	70	58,7	2,2	
A9-20H200F	●		6F	20	18	87	80,85	79,48	62	70	58,7	2,44	
A9-21H200F	●		6F	21	18	91	84,89	83,52	65	70	58,7	2,7	
A9-22H200F	●		6F	22	18	93	88,94	87,56	68	70	58,7	2,97	
A9-23H200F	●		6F	23	18	97	92,98	91,61	72	70	58,7	3,25	
A9-24H200F	●		6F	24	18	103	97,03	95,65	72	70	58,7	3,56	
A9-25H200F	●		6F	25	18	106	101,06	99,69	72	70	58,7	3,81	
A9-26H200F	●		6F	26	18	111	105,11	103,73	80	70	58,7	4,18	
A9-27H200F	●		6F	27	18	115	109,15	107,78	80	70	58,7	4,49	
A9-28H200F	●		6F	28	18	119	113,19	111,82	80	70	58,7	4,81	
A9-29H200F	●		6F	29	18	123	117,23	115,86	80	70	58,7	5,14	
A9-30H200F	●		6F	30	18	127	121,29	119,9	80	70	58,7	5,47	
A9-32H200F	●		6F	32	18	135	129,36	127,99	80	70	58,7	6,17	

Produits associés**A8-H200** Page 228**A8-H200-CH**
Page 255**MA A9-H200**
Page 289


Poulie dentée monobloc

Pas 12,7 mm (1/2") pour courroie largeur 50,8 mm

Illustration technique et photo, voir page 264.

● Délai maîtrisé ○ Contactez-nous

■ Exemple de commande **A9-14H200F** Référence

		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg
A9-33H200F	●	6F	33	18	140	133,4	132,03	80	70	58,7	6,56
A9-34H200F	●	6F	34	18	143	137,45	136,07	80	70	58,7	6,94
A9-35H200F	●	6F	35	18	148	141,49	140,12	80	70	58,7	7,34
A9-36H200F	●	6F	36	18	152	145,53	144,16	80	70	58,7	7,75
A9-38H200F	●	6F	38	18	158	153,62	152,24	80	70	58,7	8,62
A9-40H200F	●	6F	40	18	168	161,7	160,33	80	70	58,7	9,5
Fonte											
A9-44H200F	●	6VF	44	18	184	177,87	176,5	80	70	58,7	5,14
A9-45H200F	●	6VF	45	18	192	181,91	180,54	80	70	58,7	5,38
A9-48H200F	●	6VF	48	24	200	194,04	192,67	90	75	58,7	6,29
A9-50H200	●	6A	50	24	-	202,13	200,75	90	75	58,7	6,68
A9-52H200	●	6A	52	24	-	210,21	208,84	90	75	58,7	6,81
A9-58H200	●	6A	58	24	-	234,47	233,09	90	75	58,7	7,26
A9-60H200	●	6A	60	24	-	242,55	241,18	100	75	58,7	8,25
A9-70H200	●	6A	70	28	-	282,98	281,61	100	75	58,7	9,2
A9-72H200	●	6A	72	28	-	291,06	289,69	120	75	58,7	11,09
A9-84H200	●	6A	84	28	-	339,57	338,2	120	75	58,7	12,63
A9-96H200	●	6A	96	28	-	388,08	386,71	120	75	58,7	14,51
A9-120H200	●	6A	120	28	-	485,1	483,73	120	75	58,7	19,15