

MICHAUD CHAILLYELEMENTS
DE TRANSMISSIONmodèle **A9-H300**

Poulie dentée monobloc

Pas 12,7 mm (1/2") pour courroie largeur 76,2 mm

Illustration technique et photo, voir page 264.

MATIÈRE

- Acier.
- Fonte.

		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	Référence
	<input type="radio"/>											Exemple de commande A9-14H300F
Acier	<input checked="" type="radio"/>											
A9-14H300F	<input checked="" type="radio"/>	6F	14	18	63	56,59	55,22	40	100	85,7	1,64	
A9-15H300F	<input checked="" type="radio"/>	6F	15	18	66	60,64	59,27	45	100	85,7	1,91	
A9-16H300F	<input checked="" type="radio"/>	6F	16	18	71	64,68	63,31	45	100	85,7	2,16	
A9-17H300F	<input checked="" type="radio"/>	6F	17	18	75	68,72	67,35	45	100	85,7	2,43	
A9-18H300F	<input checked="" type="radio"/>	6F	18	18	79	72,77	71,39	55	100	85,7	2,8	
A9-19H300F	<input checked="" type="radio"/>	6F	19	18	83	76,81	75,44	60	100	85,7	3,16	
A9-20H300F	<input checked="" type="radio"/>	6F	20	18	87	80,85	79,48	62	100	85,7	3,5	
A9-21H300F	<input checked="" type="radio"/>	6F	21	18	91	84,89	83,52	65	100	85,7	3,87	
A9-22H300F	<input checked="" type="radio"/>	6F	22	18	93	88,94	87,56	68	100	85,7	4,26	
A9-23H300F	<input checked="" type="radio"/>	6F	23	18	97	92,98	91,61	72	100	85,7	4,68	
A9-24H300F	<input checked="" type="radio"/>	6F	24	18	103	97,03	95,65	72	100	85,7	5,08	
A9-25H300F	<input checked="" type="radio"/>	6F	25	18	106	101,06	99,69	72	100	85,7	5,45	
A9-26H300F	<input checked="" type="radio"/>	6F	26	18	111	105,11	103,73	80	100	85,7	6,01	
A9-27H300F	<input checked="" type="radio"/>	6F	27	18	115	109,15	107,78	80	100	85,7	6,45	
A9-28H300F	<input checked="" type="radio"/>	6F	28	18	119	113,19	111,82	80	100	85,7	6,91	
A9-30H300F	<input checked="" type="radio"/>	6F	30	18	127	121,29	119,9	80	100	85,7	7,9	
A9-32H300F	<input checked="" type="radio"/>	6F	32	18	135	129,36	127,99	80	100	85,7	8,92	
A9-33H300F	<input checked="" type="radio"/>	6F	33	18	140	133,4	132,03	80	100	85,7	9,46	

Produits associés


A8-H300 Page 228

MA A9-H300
Page 290

Poulie dentée monobloc

Pas 12,7 mm (1/2") pour courroie largeur 76,2 mm

Illustration technique et photo, voir page 264.

	● Délai maîtrisé	○ Contactez-nous										Référence
			Exemple de commande	A9-14H300F								
		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	
A9-34H300F	●	6F	34	18	143	137,45	136,07	80	100	85,7	10,04	
A9-35H300F	●	6F	35	18	148	141,49	140,12	80	100	85,7	10,62	
A9-36H300F	●	6F	36	18	152	145,53	144,16	80	100	85,7	11,24	
A9-38H300F	●	6F	38	18	158	153,62	152,24	80	100	85,7	12,44	
A9-40H300F	●	6F	40	18	168	161,7	160,33	80	100	85,7	13,8	
Fonte												
A9-44H300F	●	6VF	44	24	184	177,87	176,5	80	100	85,7	7,22	
A9-48H300F	●	6VF	48	24	200	194,04	192,67	90	100	85,7	8,6	
A9-50H300	●	6A	50	24	-	202,13	200,75	90	100	85,7	8,99	
A9-58H300	●	6A	58	24	-	234,47	233,09	90	100	85,7	10,04	
A9-60H300	●	6A	60	24	-	242,55	241,18	100	100	85,7	11,18	
A9-72H300	●	6A	72	28	-	291,06	289,69	120	100	85,7	15,07	
A9-84H300	●	6A	84	28	-	339,57	338,2	120	100	85,7	16,97	
A9-96H300	●	6A	96	28	-	388,08	386,71	120	100	85,7	19,86	
A9-120H300	●	6A	120	28	-	485,1	483,73	120	100	85,7	25,91	