


Poulie dentée monobloc

Pas 9,525 mm (3/8") pour courroie largeur 12,7 mm

Illustration technique et photo, voir page 264.

MATIÈRE

- Acier.
- Fonte.

	● Délai maîtrisé	○ Contactez-nous										Référence
			Exemple de commande	A9-10L050F								
		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	
Acier												
A9-10L050F	●	6F	10	8	36	30,32	29,56	20	28	19	0,11	
A9-11L050F	●	6F	11	8	38	33,35	32,59	24	30	19	0,14	
A9-12L050F	●	6F	12	8	42	36,38	35,62	24	30	19	0,17	
A9-13L050F	●	6F	13	8	44	39,41	38,65	28	30	19	0,21	
A9-14L050F	●	6F	14	8	48	42,44	41,68	28	30	19	0,24	
A9-15L050F	●	6F	15	8	51	45,48	44,72	34	30	19	0,29	
A9-16L050F	●	6F	16	8	54	48,51	47,75	36	32	19	0,33	
A9-17L050F	●	6F	17	10	57	51,54	50,78	36	32	19	0,38	
A9-18L050F	●	6F	18	10	60	54,57	53,81	40	32	19	0,44	
A9-19L050F	●	6F	19	10	63	57,61	56,84	40	32	19	0,47	
A9-20L050F	●	6F	20	10	66	60,64	59,88	40	32	19	0,51	
A9-21L050F	●	6F	21	10	71	63,67	62,91	45	32	19	0,6	
A9-22L050F	●	6F	22	10	75	66,7	65,94	45	32	19	0,64	
A9-23L050F	●	6F	23	10	79	69,73	68,97	55	32	19	0,78	
A9-24L050F	●	6F	24	10	79	72,77	72	55	32	19	0,81	
A9-25L050F	●	6F	25	10	83	75,8	75,04	58	32	19	0,89	
A9-26L050F	●	6F	26	12	87	78,83	78,07	58	32	19	0,94	
A9-27L050F	●	6F	27	12	87	81,86	81,1	58	32	19	0,99	
A9-28L050F	●	6F	28	12	91	84,89	84,13	58	32	19	1,04	

Produits associés



A8-L050 Page 227



A8-L050-CH
Page 255



A9-BD-L050
Page 343




MA A9-L050
Page 284

MICHAUD CHAILLYELEMENTS
DE TRANSMISSIONmodèle **A9-L050**

Poulie dentée monobloc

Pas 9,525 mm (3/8") pour courroie largeur 12,7 mm

Illustration technique et photo, voir page 264.

	● Délai maîtrisé	○ Contactez-nous										Référence
		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	Exemple de commande A9-10L050F
A9-30L050F	●	6F	30	12	97	90,96	90,2	70	32	19	1,17	
A9-32L050F	●	6F	32	12	103	97,03	96,26	70	32	19	1,41	
A9-33L050F	●	6F	33	12	106	100,05	99,29	70	32	19	1,49	
A9-34L050F	●	6F	34	12	111	103,08	102,32	70	32	19	1,57	
A9-35L050F	●	6F	35	12	111	106,12	105,35	70	32	19	1,62	
A9-36L050F	●	6F	36	12	115	109,15	108,39	70	32	19	1,7	
A9-40L050F	●	6F	40	12	127	121,29	120,51	70	32	19	2,03	
A9-42L050F	●	6F	42	12	135	127,34	126,58	70	32	19	2,21	
A9-44L050F	●	6F	44	12	140	133,4	132,64	70	32	19	2,38	
A9-45L050F	●	6F	45	12	143	136,44	135,67	70	32	19	2,48	
A9-48L050F	●	6F	48	12	152	145,53	144,77	70	32	19	2,78	
Fonte												
A9-50L050	●	6A	50	14	-	151,6	150,83	70	32	19	1,74	
A9-52L050	●	6A	52	14	-	157,66	156,9	70	32	19	1,8	
A9-56L050	●	6A	56	14	-	169,79	169,02	70	32	19	1,87	
A9-57L050	●	6A	57	14	-	172,82	172,06	70	32	19	1,88	
A9-60L050	●	6A	60	14	-	181,91	181,15	75	42	19	2,41	
A9-72L050	●	6A	72	14	-	218,29	217,53	75	42	19	2,82	
A9-84L050	●	6A	84	14	-	254,68	253,92	75	42	19	3,08	
A9-96L050	●	6A	96	14	-	291,06	290,3	75	42	19	3,42	