


Poulie dentée monobloc

Pas 9,525 mm (3/8") pour courroie largeur 19,05 mm

Illustration technique et photo, voir page 264.

MATIÈRE

- Acier.
- Fonte.

	● Délai maîtrisé	○ Contactez-nous											Référence
			Exemple de commande	A9-10L075F									
		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg		
Acier													
A9-10L075F	●	6F	10	8	36	30,32	29,56	20	38	25,4	0,14		
A9-11L075F	●	6F	11	8	38	33,35	32,59	24	38	25,4	0,18		
A9-12L075F	●	6F	12	8	42	36,38	35,62	24	38	25,4	0,22		
A9-13L075F	●	6F	13	8	44	39,41	38,65	28	38	25,4	0,26		
A9-14L075F	●	6F	14	8	48	42,44	41,68	28	38	25,4	0,3		
A9-15L075F	●	6F	15	8	51	45,48	44,72	34	38	25,4	0,37		
A9-16L075F	●	6F	16	8	54	48,51	47,75	36	38	25,4	0,43		
A9-17L075F	●	6F	17	10	57	51,54	50,78	36	38	25,4	0,46		
A9-18L075F	●	6F	18	10	60	54,57	53,81	40	38	25,4	0,54		
A9-19L075F	●	6F	19	10	63	57,61	56,84	40	38	25,4	0,58		
A9-20L075F	●	6F	20	10	66	60,64	59,88	40	38	25,4	0,64		
A9-21L075F	●	6F	21	10	71	63,67	62,91	45	38	25,4	0,71		
A9-22L075F	●	6F	22	10	75	66,7	65,94	45	38	25,4	0,79		
A9-23L075F	●	6F	23	10	79	69,73	68,97	55	38	25,4	0,94		
A9-24L075F	●	6F	24	10	79	72,77	72	55	38	25,4	1		
A9-25L075F	●	6F	25	10	83	75,8	75,04	58	38	25,4	1,1		
A9-26L075F	●	6F	26	12	87	78,83	78,07	58	38	25,4	1,16		
A9-27L075F	●	6F	27	12	87	81,86	81,1	58	38	25,4	1,22		
A9-28L075F	●	6F	28	12	91	84,89	84,13	58	38	25,4	1,3		

Produits associés



A8-L075 Page 227



A8-L075-CH
Page 255



A9-BD-L075
Page 343




MA A9-L075
Page 285

MICHAUD CHAILLYELEMENTS
DE TRANSMISSIONmodèle **A9-L075**

Poulie dentée monobloc

Pas 9,525 mm (3/8") pour courroie largeur 19,05 mm

Illustration technique et photo, voir page 264.

		Schéma	Nombre de dents	d ₁	d ₂	d ₃	d ₄	d ₅	l ₁	l ₂	Poids kg	Référence	
A9-30L075F	●	6F	30	12	97	90,96	90,2	70	38	25,4	1,47	Exemple de commande A9-10L075F	
A9-32L075F	●	6F	32	12	103	97,03	96,26	70	38	25,4	1,75		
A9-33L075F	●	6F	33	12	106	100,05	99,29	70	38	25,4	1,85		
A9-34L075F	●	6F	34	12	111	103,08	102,32	70	38	25,4	1,93		
A9-35L075F	●	6F	35	12	111	106,12	105,35	70	38	25,4	2,03		
A9-36L075F	●	6F	36	12	115	109,15	108,39	70	38	25,4	2,14		
A9-40L075F	●	6F	40	12	127	121,29	120,51	70	38	25,4	2,56		
A9-42L075F	●	6F	42	12	135	127,34	126,58	70	38	25,4	2,81		
A9-44L075F	●	6F	44	12	140	133,4	132,64	70	38	25,4	3,02		
A9-45L075F	●	6F	45	12	143	136,44	135,67	70	38	25,4	3,16		
A9-48L075F	●	6F	48	12	152	145,53	144,77	70	38	25,4	3,57		
Fonte													
A9-50L075	●	6A	50	14	-	151,6	150,83	70	38	25,4	2,1		
A9-52L075	●	6A	52	14	-	157,66	156,9	70	38	25,4	2,13		
A9-56L075	●	6A	56	14	-	169,79	169,02	70	38	25,4	2,27		
A9-57L075	●	6A	57	14	-	172,82	172,06	70	38	25,4	2,28		
A9-60L075	●	6A	60	14	-	181,91	181,15	75	45	25,4	2,7		
A9-72L075	●	6A	72	14	-	218,29	217,53	75	45	25,4	3,19		
A9-84L075	●	6A	84	14	-	254,68	253,92	75	45	25,4	3,64		
A9-96L075	●	6A	96	14	-	291,06	290,3	75	45	25,4	4,04		