

**MICHAUD CHAILLY**ELEMENTS  
DE TRANSMISSIONmodèle **MA A9-L050**


# Poulie dentée à moyeu amovible

## Pas 9,525 mm (3/8") pour courroie largeur 12,7 mm

Illustration technique et photo, voir pages 282 / 283.

**MATIÈRE**

- Acier.
- Fonte.

		Schéma	Nombre de dents	Alésage maxi du moyeu	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	Référence	
													Exemple de commande	<b>A9-18L050-1108</b>
													Poids kg	
<b>Acier</b>														
A9-18L050-1108	●	8F	18	28	60	54,57	53,81	45	-	22	19	3	0,2	
A9-19L050-1108	●	8F	19	28	63	57,61	56,84	45	-	22	19	3	0,23	
A9-20L050-1108	●	8F	20	28	66	60,64	59,88	48	-	22	19	3	0,27	
A9-21L050-1108	●	8F	21	28	71	63,67	62,91	48	-	22	19	3	0,3	
A9-22L050-1108	●	8F	22	28	75	66,7	65,94	51	-	22	19	3	0,34	
A9-23L050-1108	●	8F	23	28	79	69,73	68,97	54	-	22	19	3	0,4	
A9-24L050-1108	●	8F	24	28	79	72,77	72	54	-	22	19	3	0,45	
A9-25L050-1108	●	8F	25	28	83	75,8	75,04	56	-	22	19	3	0,5	
A9-26L050-1108	●	8F	26	28	87	78,83	78,07	60	-	22	19	3	0,55	
A9-27L050-1108	●	8F	27	28	87	81,86	81,1	62	-	22	19	3	0,6	
A9-28L050-1108	●	8F	28	28	91	84,89	84,13	65	-	22	19	3	0,65	
A9-30L050-1108	●	8F	30	28	97	90,96	90,2	70	-	22	19	3	0,8	
A9-32L050-1108	●	8F	32	28	103	97,02	96,26	74	-	22	19	3	0,98	
A9-36L050-1108	●	8F	36	28	115	109,15	108,39	85	-	22	19	3	1,2	
A9-40L050-1610	●	8F	40	42	127	121,28	120,51	97	-	25	19	6	1,4	
A9-48L050-1610	●	8WF	48	42	152	145,53	144,77	88	120	25	19	6	2,3	
A9-60L050-1610	●	7W	60	42	-	181,91	181,15	92	166	25	19	3	2,2	
<b>Fonte</b>														
A9-72L050-1610	●	7A	72	42	-	218,3	217,53	92	202	25	19	3	2,1	
A9-84L050-1610	●	7A	84	42	-	254,68	253,9	92	236	25	19	3	2,46	
A9-96L050-2012	●	7A	96	50	-	291,06	290,3	106	270	32	19	6,5	3,36	
A9-120L050-2012	●	7A	120	50	-	363,83	363,07	106	343	32	19	6,5	4,44	

**Produits associés****A5-MA** Page 520**A8-L050** Page 227**A8-L050-CH**  
Page 255**A9-L050** Page 267