


Poulie dentée à moyeu amovible

Pas 9,525 mm (3/8") pour courroie largeur 19,05 mm

Illustration technique et photo, voir pages 282 / 283.

MATIÈRE

- Acier.
- Fonte.

		Référence											
		Exemple de commande A9-18L075-1108											
		● Délai maîtrisé ○ Contactez-nous											
		Schéma	Nombre de dents	Alésage maxi du moyeu	d ₂	d ₃	d ₄	d ₅	d ₆	l ₁	l ₂	l ₃	Poids kg
Acier													
A9-18L075-1108	●	3F	18	28	60	54,57	53,81	-	-	25	25	-	0,25
A9-19L075-1108	●	3F	19	28	63	57,61	56,84	-	-	25	25	-	0,32
A9-20L075-1108	●	3F	20	28	66	60,64	59,88	-	-	25	25	-	0,35
A9-21L075-1108	●	3F	21	28	71	63,67	62,91	-	-	25	25	-	0,4
A9-22L075-1108	●	3F	22	28	75	66,7	65,94	-	-	25	25	-	0,44
A9-23L075-1108	●	3F	23	28	79	69,73	68,97	-	-	25	25	-	0,48
A9-24L075-1108	●	3F	24	28	79	72,77	72	-	-	25	25	-	0,55
A9-25L075-1108	●	3F	25	28	83	75,8	75,04	-	-	25	25	-	0,63
A9-26L075-1108	●	3F	26	28	87	78,83	78,07	-	-	25	25	-	0,66
A9-27L075-1108	●	3F	27	28	87	81,86	81,1	-	-	25	25	-	0,7
A9-28L075-1108	●	3F	28	28	91	84,89	84,13	-	-	25	25	-	0,72
A9-30L075-1108	●	3F	30	28	97	90,96	90,2	-	-	25	25	-	0,93
A9-32L075-1108	●	3F	32	28	103	97,02	96,26	-	-	25	25	-	1,1
A9-36L075-1610	●	3F	36	42	115	109,15	108,39	-	-	25	25	-	1,2
A9-40L075-1610	●	3F	40	42	127	121,28	120,51	-	-	25	25	-	1,7
A9-48L075-1610	●	3WF	48	42	152	145,53	144,77	92	120	25	25	-	2,6
A9-60L075-1610	●	3W	60	42		181,91	181,15	92	166	25	25	-	3
Fonte													
A9-72L075-1610	●	3A	72	42	-	218,3	217,53	92	202	25	25	-	2,33
A9-84L075-2012	●	7A	84	50	-	254,68	253,9	106	236	32	25	3,5	3,55
A9-96L075-2012	●	7A	96	50	-	291,06	290,3	106	270	32	25	3,5	3,95
A9-120L075-2012	●	7A	120	50	-	363,83	363,07	106	343	32	25	3,5	5,61

Produits associés

A5-MA Page 520

A8-L075 Page 227

A8-L075-CH
Page 255

A9-L075 Page 269