

MICHAUD CHAILLYELEMENTS
DE TRANSMISSIONmodèle **MA A9-L100**


Poulie dentée à moyeu amovible

Pas 9,525 mm (3/8") pour courroie largeur 25,4 mm

Illustration technique et photo, voir pages 282 / 283.

MATIÈRE

- Acier.
- Fonte.

		Schéma	Nombre de dents	Alésage maxi du moyeu	d ₂	d ₃	d ₄	d ₅	d ₆	l ₁	l ₂	l ₃	Référence
													Exemple de commande
													Poids kg
Acier													
A9-18L100-1108	●	5F	18	28	60	54,57	53,81	-	38	22	31	9	0,2
A9-19L100-1108	●	5F	19	28	63	57,61	56,84	-	38	22	31	9	0,32
A9-20L100-1108	●	5F	20	28	66	60,64	59,88	-	45	22	31	9	0,41
A9-21L100-1108	●	5F	21	28	71	63,67	62,91	-	45	22	31	9	0,45
A9-22L100-1108	●	5F	22	28	75	66,7	65,94	-	48	22	31	9	0,47
A9-23L100-1108	●	5F	23	28	79	69,73	68,97	-	52	22	32	10	0,5
A9-24L100-1108	●	5F	24	28	79	72,77	72	-	52	22	32	10	0,64
A9-25L100-1108	●	5F	25	28	83	75,8	75,04	-	54	22	32	10	0,68
A9-26L100-1108	●	5F	26	28	87	78,83	78,07	-	60	22	32	10	0,7
A9-27L100-1108	●	5F	27	28	87	81,86	81,1	-	60	22	32	10	0,83
A9-28L100-1108	●	5F	28	28	91	84,89	84,13	-	65	22	32	10	0,85
A9-30L100-1210	●	5F	30	32	97	90,96	90,2	-	71	25	32	7	0,9
A9-32L100-1210	●	5F	32	32	103	97,02	96,26	-	75	25	32	7	1,05
A9-36L100-1610	●	5F	36	42	115	109,15	108,39	-	86	25	32	7	1,4
A9-40L100-1610	●	5F	40	42	127	121,28	120,51	-	96	25	32	7	1,65
A9-48L100-1610	●	5WF	48	42	152	145,53	144,77	92	120	25	32	7	2,8
A9-60L100-1610	●	9W	60	42		181,91	181,15	92	166	25	32	3,5	2,7
Fonte													
A9-72L100-2012	●	3A	72	50	-	218,3	217,53	106	202	32	32	-	2,96
A9-84L100-2012	●	3A	84	50	-	254,68	253,9	106	236	32	32	-	3,87
A9-96L100-2012	●	3A	96	50	-	291,06	290,3	106	270	32	32	-	4,64
A9-120L100-2012	●	3A	120	50	-	363,83	363,07	106	343	32	32	-	6,37

● Délai maîtrisé ○ Contactez-nous

■ Exemple de commande **A9-18L100-1108****Produits associés****A5-MA** Page 520**A8-L100** Page 227**A8-L100-CH**
Page 255**A9-L100** Page 271