

Poulie dentée à moyeu amovible HTD®

Pas 8 mm pour courroie largeur 20 mm

Illustration technique et photo, voir pages 302 / 303.


MATIÈRE

- Acier.
- Fonte grise.

Référence

■ Exemple de commande **A9-22-8M20-1008**

● Délai maîtrisé ○ Contactez-nous

		Schéma	Nombre de dents	N° de moyeu	Alésage maxi du moyeu	d ₂	d ₃	d ₄	d ₅	d ₆	l ₁	l ₂	l ₃	Poids kg
Acier														
A9-22-8M20-1008	●	16F	22	1008	25	60	56,02	54,65	-	37	22	28	6	0,25
A9-24-8M20-1108	●	16F	24	1108	25	66	61,11	59,74	-	44	22	28	6	0,3
A9-26-8M20-1108	●	16F	26	1108	25	71	66,21	64,84	-	45	22	28	6	0,36
A9-28-8M20-1108	●	16F	28	1108	25	75	71,30	70,08	-	50	22	28	6	0,45
A9-30-8M20-1108	●	16F	30	1108	25	83	76,39	75,13	-	58	22	28	6	0,55
A9-32-8M20-1610	●	16F	32	1610	42	87	81,49	80,16	-	63	25	28	3	0,43
A9-34-8M20-1610	●	16F	34	1610	42	91	86,58	85,21	-	64	25	28	3	0,57
A9-36-8M20-1610	●	16F	36	1610	42	98	91,67	90,30	-	68	25	28	3	0,7
A9-38-8M20-1610	●	16F	38	1610	42	103	96,77	95,39	-	72	25	28	3	0,82
A9-40-8M20-1610	●	16F	40	1610	42	106	101,86	100,49	-	76	25	28	3	1,1
A9-44-8M20-2012	●	10F	44	2012	50	119	112,05	110,67	92	-	32	28	4	1,2
A9-48-8M20-2012	●	10F	48	2012	50	127	122,23	120,86	96	-	32	28	4	1,65
A9-56-8M20-2012	●	10F	56	2012	50	148	142,60	141,23	110	-	32	28	4	2,5
A9-64-8M20-2012	●	11F	64	2012	50	168	162,97	161,60	110	137	32	28	4	2,6
A9-72-8M20-2012	●	11F	72	2012	50	192	183,35	181,97	110	158	32	28	4	3,4
Fonte														
A9-80-8M20-2012	●	11	80	2012	50	-	203,72	202,35	110	180	32	28	4	3,6
A9-90-8M20-2012	●	11	90	2012	50	-	229,18	227,81	110	204	32	28	4	4,1

■ Produits associés



A5-MA Page 520



A8-8M20 Page 236



A9-8M20 Page 295